



7PIN DIP ZERO-CROSS PHOTO POWER TRIAC PHOTOCOUPLER ELRX213 Series



LED Anode	2
LED Cathode	1, 3, 4
Triac Gate	5
Triac T1	6
Triac T2,,	8

Features

- Low trigger current I_{FT} 10mA
- Peak off state voltage 600V
- Load current 0.3 , 0.6 , 0.9 , 1.2A
- Wide operating temperature range of -40°C to 85°C
- High isolation voltage between input and output (Viso=5000 Vrms)
- Zero voltage crossing
- Compliance with EU REACH
- Pb free and RoHS compliant
- UL and cUL approved(No. E214129)
- VDE approved (No. 40028391)
- SEMKO approved
- NEMKO approved
- DEMKO approved
- FIMKO approved
- CQC approved

Description

The ELRX213 series of devices are each consist of a GaAs infrared emitting diode optically coupled to a monolithic silicon zero cross photo triac and a main output triac. They are designed for interfacing between electronic controls and loads to control inductive for 115 to 240 VAC operations. They are packaged in 8pin DIP package and available in surface mount SMD option.

Applications

- Home appliances
- Industrial equipment
- Switching motors, fans, heaters, solenoids and valces.
- Power control such as lighting and temperature control

Absolute Maximum Ratings ($T_A=25^{\circ}\text{C}$, unless otherwise specified)

Parameter		Symbol	Rating	Unit
Input	Forward Current	I_F	60	mA
	Reverse Voltage	V_R	6	V
	Peak Forward Current* ¹	I_{FP}	1	A
Output	Repetitive Peak Off-state Voltage* ²	V_{DRM}	600	V
		ELR0213	0.3	
	On-state RMS Current	ELR1213	0.6	A
		ELR2213	0.9	
		ELR3213	1.2	
	Non-repetitive Surge Current* ³	ELR0213	3	A
		ELR1213	6	
		ELR2213	9	
		ELR3213	12	
	Isolation Voltage* ⁴	V_{ISO}	5000	V_{rms}
Storage Temperature	T_{STG}	-40 to 125	$^{\circ}\text{C}$	
Operating Temperature	T_{OPR}	-40 to 85	$^{\circ}\text{C}$	
Soldering Temperature* ⁵	T_{SOL}	260	$^{\circ}\text{C}$	

- Notes:
- *1 $f=100\text{Hz}$, Duty Cycle = 0.1%
 - *2 Sine wave, 50 to 60Hz, $I_{FT}=0\text{mA}$.
 - *3 $f=60\text{Hz}$, one cycle.
 - *4 AC for 1 minute, R.H.= 40 ~ 60% R.H. In this test, pins 1, 2, 3, 4 are shorted together, and pins 5, 6, 7, 8 are shorted together.
 - *5 For 10 seconds
 - *6 Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of this document. Exposure to absolute maximum ratings for extended periods of the time can adversely affect reliability. The absolute maximum Rating s are stress only $T_A=25^{\circ}\text{C}$ unless otherwise specified.

Electro-Optical Characteristics (T_A=25°C)

	Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Input	Forward Voltage	V _F	I _F = 20mA	-	1.2	1.4	V
	Reverse Current	I _R	V _R = 6V	-	-	10	uA
Output	Repetitive Peak Off-state Current	I _{DRM}	I _F = 0mA, V _{DRM} = 600V	-	-	100	uA
	On-state Voltage	V _{TM}	I _F = 10mA, I _{TM} = MAX.	-	-	2.5	V
	Critical Rate of Rise of Off-state Voltage	dv/dt	V _{DRM} = 600V × 1/√2	200	-	-	V/us
	Holding Current	I _H	-	-	-	25	mA
	Inhibit Voltage (MT1-MT2 voltage above which device will not trigger)	V _{INH}	I _F = Rated I _{FT}	-	-	50	V
	Transfer Characteristics	Minimum Trigger Current	I _{FT}	V _D = 6V, R _L = 100Ω	-	-	10
Turn On Time		T _{on}	I _F = 20 mA, V _D = 6V, R _L = 100Ω,	-	-	10	us
Isolation Resistance		R _{I-O}	V _{I-O} = 500V DC, 40 to 60%RH	-	5×10 ¹¹	-	Ω

Typical Electro-Optical Characteristics Curves

Fig.1 ON-state Current vs. Ambient Temperature




Figure 2. On Voltage vs. Ambient Temperature




Figure 3. Trigger LED Current vs Ambient Temperature




Figure 4. LED Dropout Voltage vs Ambient Temperature




Figure 5. Turn on Time vs LED Current




Figure 6. Off-state Leakage Current vs Load Voltage




Figure 7. Holding Current vs. Ambient Temperature





Figure 8. Inhibit Voltage vs. Ambient Temperature



Order Information

Part Number




ELRX213Y(Z)-V

Note




- X = (0 or 1 or 2 or 3) for ELX213 part no.
- Y = Lead form option (S, S1, M or none)
- Z = Tape and reel option (TA, TB or none).
- V = VDE (optional)

Option	Description	Packing quantity
None	Standard DIP-8	45 units per tube
M	Wide lead bend (0.4 inch spacing)	45 units per tube
S (TA)	Surface mount lead form + TA tape & reel option	1000 units per reel
S (TB)	Surface mount lead form + TB tape & reel option	1000 units per reel
S1 (TA)	Surface mount lead form (low profile) + TA tape & reel option	1000 units per reel
S1 (TB)	Surface mount lead form (low profile) + TB tape & reel option	1000 units per reel


Package Dimension
Standard DIP Type




Option M Type




Option S Type




Option S1 Type



Recommended pad layout for surface mount leadform



Device Marking





Notes

- T denotes Factory
 - No code : made in China
 - T : made in Taiwan
- EL denotes EVERLIGHT
- RX223 denotes Device Number(X = 0 or 1 or 2 or 3 for ELX213 part no.)
- Y denotes 1 digit Year code
- WW denotes 2 digit Week code
- V denotes VDE (optional)



Tape & Reel Packing Specifications

Option TA




Direction of feed from reel

Option TB



Direction of feed from reel

Tape dimension




Dimension No.	A	B	Do	D1	E	F
Dimension(mm)	10.4±0.1	10.0±0.1	1.5+0.1/-0	1.5±0.25/-0	1.75±0.1	7.5±0.1
Dimension No.	Po	P1	P2	t	W	K
Dimension(mm)	4.0±0.1	12.0±0.1	2.0±0.05	0.4±0.05	16.0±0.3/	4.5±0.1

Precautions for Use

1. Soldering Condition

1.1 (A) Maximum Body Case Temperature Profile for evaluation of Reflow Profile



Note:

Reference: IPC/JEDEC J-STD-020D

Preheat

Temperature min (T_{smin})	150 °C
Temperature max (T_{smax})	200°C
Time (T_{smin} to T_{smax}) (t_s)	60-120 seconds
Average ramp-up rate (T_{smax} to T_p)	3 °C/second max

Other

Liquidus Temperature (T_L)	217 °C
Time above Liquidus Temperature (t_L)	60-100 sec
Peak Temperature (T_p)	260°C
Time within 5 °C of Actual Peak Temperature: $T_p - 5^\circ\text{C}$	30 s
Ramp- Down Rate from Peak Temperature	6°C /second max.
Time 25°C to peak temperature	8 minutes max.
Reflow times	3 times

DISCLAIMER

1. Above specification may be changed without notice. EVERLIGHT will reserve authority on material change for above specification.
2. The graphs shown in this datasheet are representing typical data only and do not show guaranteed values.
3. When using this product, please observe the absolute maximum ratings and the instructions for use outlined in these specification sheets. EVERLIGHT assumes no responsibility for any damage resulting from use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification sheets.
4. These specification sheets include materials protected under copyright of EVERLIGHT. Reproduction in any form is prohibited without the specific consent of EVERLIGHT.
5. This product is not intended to be used for military, aircraft, automotive, medical, life sustaining or life saving applications or any other application which can result in human injury or death. Please contact authorized Everlight sales agent for special application request.
6. Statements regarding the suitability of products for certain types of applications are based on Everlight's knowledge of typical requirements that are often placed on Everlight products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Everlight's terms and conditions of purchase, including but not limited to the warranty expressed therein.