

**Low on Resistance / Low Voltage 1 A LDO for Automotive Applications**

NO.EC-265-190408

**OUTLINE**

The RP132x Series are voltage-regulators with a built-in low ON-resistance transistor and output current is 1A capability. These ICs have two versions: fixed output voltage type and externally adjustable output voltage type. The minimum output voltage can be set from 1.4V. Otherwise, the load regulation of RP132x has much improved when compared with conventional regulators. It's Typ.5mV at  $I_{OUT}=0.1mA$  to 1A.

Each of these ICs consists of a voltage reference unit, an error amplifier, a resistor net for setting output voltage, current limit circuits to prevent over-current and a thermal-shutdown circuit. A standby mode with ultra low supply current can be realized with the chip enable function.

The packages for these ICs are SOT-89-5, HSOP-6J and TO-252-5-P2. They range from high-density mounting to ultra high wattage.

**FEATURES**


- Input Voltage Range (Maximum Rating)..... 1.4V to 6.5V (7V)
- Operating Temperature Range ..... -40°C to 105°C
- Output Current ..... Min. 1A
- Supply Current ..... Typ. 65µA
- Standby Current ..... Typ. 0.15µA
- Output Voltage Range..... 0.8V, 1.05V, 1.2V, 1.5V, 1.8V, 2.5V, 3.0V, 3.3V, 5.0V  
\*Contact our sales representatives for other voltages.  
Adjustable Output Voltage Type: 0.8V to 5.5V
- Dropout Voltage ..... Typ. 0.52V ( $V_{OUT}=3.0V$ ,  $I_{OUT}=1A$ )
- Ripple Rejection..... Typ. 70dB ( $f=1kHz$ ,  $V_{OUT}=3.0V$ )
- Output Voltage Accuracy..... ±1.0%
- Output Voltage Temperature-Drift Coefficient ..... Typ. ±60ppm/°C
- Line Regulation ..... Typ. 0.052%/V
- Load Regulation ..... Typ. 3mV at  $I_{OUT}=300mA$ , Typ. 5mV at  $I_{OUT}=1A$
- Packages ..... SOT-89-5, HSOP-6J, TO-252-5-P2
- Inrush Current Limit Circuit ..... Typ. 500mA  
B/D version: Inrush current limit time is 500µs.
- Fold-Back Protection Circuit ..... Typ. 250mA (Current at short mode)
- Thermal Shutdown Circuit ..... Thermal Shutdown Temperature: Typ. 165°C  
Released Temperature: Typ. 95°C
- Auto Discharge Function ..... D version
- Ceramic capacitors are recommended to be used with this IC ..... 2.2µF or more ( $V_{OUT} \leq 3.6V$ )  
4.7µF or more ( $V_{OUT} > 3.6V$ )

**APPLICATIONS**


- Power source for accessories such as car audios, car navigation systems, and ETC systems
- Power source for control units including EV inverter and charge control.

## BLOCK DIAGRAMS


- Fixed Output Voltage Type (HSOP-6J / SOT-89-5)



- Fixed Output Voltage Type (TO-252-5-P2)



- Adjustable Output Voltage Type (HSOP-6J / SOT-89-5 / TO-252-5-P2)



## SELECTION GUIDE

The output voltage, the auto discharge function\*, and the package type for the ICs can be selected at the user's request.

Product Name	Package	Quantity per Reel	Pb Free	Halogen Free
RP132H001*-T1-#E	SOT-89-5	1,000 pcs	Yes	Yes
RP132Hxx2*-T1-#E				
RP132S001*-E2-#E	HSOP-6J	1,000 pcs	Yes	Yes
RP132Sxx2*-E2-#E				
RP132J001*-T1-#E	TO-252-5-P2	3,000 pcs	Yes	Yes
RP132Jxx1*-T1-#E				

RP132x001x is the adjustable output voltage type.

xx: Specify the set output voltage ( $V_{SET}$ ) of the fixed output voltage type.

0.8V(08), 1.2V(12), 1.5V(15), 1.8V(18), 2.5V(25), 3.0V(30), 3.3V(33), 5.0V(50)

1.05V(RP132x10xx5)

\*Contact our sales representatives for other voltages.

\*: The auto discharge function at off state options are as follows.

(B) without auto discharge function\* at off state


(D) with auto discharge function\* at off state

# : Specify Automotive Class Code

	Operating Temperature Range	Guaranteed Specs Temperature Range	Screening
A	-40°C to 105°C	25°C	High Temperature
J	-40°C to 105°C	-40°C to 105°C	High and Low Temperature

\* Auto-discharge function quickly lowers the output voltage to 0V, when the chip enable signal is switched from the active mode to the standby mode, by releasing the electrical charge accumulated in the external capacitor.

## PIN DESCRIPTIONS



### • SOT-89-5

Pin No.	Symbol	Pin Description
1	CE	Chip Enable Pin ("H" Active) (RP132Hxx2B/D)
	V <sub>FB</sub>	Feed Back Pin (RP132H001B/D)
2	GND	Ground Pin
3	GND	Ground Pin (RP132Hxx2B/D)
	CE	Chip Enable Pin ("H" Active) (RP132H001B/D)
4	V <sub>DD</sub>	Input Pin
5	V <sub>OUT</sub>	Output Pin

When using Fixed Output Voltage Type (RP132Hxx2x), No.2 pin and No. 3 pin must be wired each other when mounted on boards. When using Adjustable Output Voltage Type (RP132H001x), please follow "Notes on Adjustable Output Voltage Type Settings".

### • HSOP-6J

Pin No.	Symbol	Pin Description
1	V <sub>OUT</sub>	Output Pin
2	GND	Ground Pin
3	GND	Ground Pin (RP132Sxx2B/D)
	V <sub>FB</sub>	Feed Back Pin (RP132S001B/D)
4	CE	Chip Enable Pin ("H" Active)
5	GND	Ground Pin
6	V <sub>DD</sub>	Input Pin

When using Fixed Output Voltage Type (RP132Hxx2x), No.2 pin, No. 3 pin, and No.5 pin must be wired each other when mounted on boards. When using Adjustable Output Voltage Type (RP132S001x), please follow "Notes on Adjustable Output Voltage Type Settings".

**● TO-252-5-P2**

Pin No.	Symbol	Pin Description
1	CE	Chip Enable Pin ("H" Active)
2	V <sub>DD</sub>	Input Pin
3	GND	Ground Pin
4	V <sub>OUT</sub>	Output Pin
5	V <sub>FB</sub>	Feed Back Pin

\*<sup>1</sup> Tab is GND level. (They are connected to the reverse side of this IC.) The tab is better to be connected to the GND, but leaving it open is also acceptable.

When using Fixed Output Voltage Type(RP132Jxx1x), V<sub>OUT</sub> pin and V<sub>FB</sub> pin should be connected. When using Adjustable Output Voltage Type (RP132J001x), please follow "Notes on the Adjustable Output Voltage Type Settings".

## ABSOLUTE MAXIMUM RATINGS

Symbol	Item			Rating	Unit
$V_{IN}$	Input Voltage			7.0	V
$V_{CE}$	Input Voltage (CE Pin)			-0.3 to 7.0	V
$V_{FB}$	Input Voltage ( $V_{FB}$ Pin)			-0.3 to 7.0	V
$V_{OUT}$	Output Voltage			-0.3 to $V_{IN}+0.3$	V
$P_D$	Power Dissipation*	SOT-89-5	JEDEC STD. 51	3200	mV
		HSOP-6J	JEDEC STD. 51	3400	
		TO-252-5-P2	JEDEC STD. 51	4800	
$T_j$	Junction Temperature			-40 to 150	°C
$T_{stg}$	Storage Temperature Range			-55 to 150	°C

\*) Refer to *PACKAGE INFORMATION* for detailed information.

### ABSOLUTE MAXIMUM RATINGS

Electronic and mechanical stress momentarily exceeded absolute maximum ratings may cause permanent damage and may degrade the life time and safety for both device and system using the device in the field. The functional operation at or over these absolute maximum ratings is not assured.

## RECOMMENDED OPERATING CONDITIONS

Symbol	Item	Rating	Unit
$V_{IN}$	Input Voltage	1.4 to 6.5	V
$T_a$	Operating Temperature Range	-40 to 105	°C

### RECOMMENDED OPERATING CONDITIONS

All of electronic equipment should be designed that the mounted semiconductor devices operate within the recommended operating conditions. The semiconductor devices cannot operate normally over the recommended operating conditions, even if they are used over such conditions by momentary electronic noise or surge. And the semiconductor devices may receive serious damage when they continue to operate over the recommended operating conditions.

## ELECTRICAL CHARACTERISTICS

$V_{IN}=V_{SET}+1.0V$ ,  $I_{OUT}=1mA$ ,  $C_{IN}=2.2\mu F$ ,  $C_{OUT}=2.2\mu F(V_{SET} \leq 3.6V)$ ,  $4.7\mu F(V_{SET} > 3.6V)$ , unless otherwise noted.  
The specifications surrounded by    are guaranteed by design engineering at  $-40^{\circ}C \leq Ta \leq 105^{\circ}C$ .

### • RP132xxxxB/D (-AE) (Fixed Output Voltage Type)

(Ta=25°C)

Symbol	Item	Conditions	Min.	Typ.	Max.	Unit
$V_{OUT}$	Output Voltage	Ta=25°C	$V_{OUT} > 1.5V$	x0.99		$\times 1.01$
			$V_{OUT} \leq 1.5V$	-15		15
	$-40^{\circ}C \leq Ta \leq 105^{\circ}C$	$V_{OUT} > 1.5V$	x0.981		$\times 1.019$	V
		$V_{OUT} \leq 1.5V$	-29		29	mV
$I_{LIM}$	Output Current Limit		1			A
$\Delta V_{OUT}/\Delta I_{OUT}$	Load Regulation	0.1mA $\leq I_{OUT} \leq 300mA$		3	20	mV
		0.1mA $\leq I_{OUT} \leq 1A$		5	60	
$V_{DIF}$	Dropout Voltage	Refer to the <i>Product-specific Electrical Characteristics</i>				
$I_{SS}$	Supply Current	$I_{OUT}=0mA$ ( $V_{IN}=6.5V$ )		65	85	$\mu A$
$I_{STANDBY}$	Standby Current	$V_{CE}=0V$ , $V_{IN}=6.5V$		0.15	0.60	$\mu A$
$\Delta V_{OUT}/\Delta V_{IN}$	Line Regulation	Set $V_{OUT}+0.5V \leq V_{IN} \leq 6.5V$ * However, $V_{IN} \geq 1.6V$		0.05	0.10	%/V
$I_{SC}$	Short Current Limit	$V_{OUT}=0V$		250		mA
$I_{PD}$	CE Pull-down Current			0.3	0.7	$\mu A$
$V_{CEH}$	CE Input Voltage "H"		1.0			V
$V_{CEL}$	CE Input Voltage "L"				0.4	V
$T_{TSD}$	Thermal Shutdown Detection Temperature	Junction Temperature		165		$^{\circ}C$
$T_{TSR}$	Thermal Shutdown Released Temperature	Junction Temperature		95		$^{\circ}C$
$R_{LOW}$	Low Output Nch Tr. ON Resistance (D version)	$V_{IN}=4.0V$ , $V_{CE}=0V$		50		$\Omega$

All test items listed under Electrical Characteristics are done under the pulse load condition ( $T_j \approx Ta = 25^{\circ}C$ ) except for Dropout Voltage and Load Regulation at 1A Output Current.

---

**RP132x**NO.EC-265-190408

---

The specifications surrounded by  are guaranteed by design engineering at  $-40^{\circ}\text{C} \leq \text{Ta} \leq 105^{\circ}\text{C}$ .

**RP132xxxxB/D (-AE) (Fixed Output Voltage Type) Product-specific Electrical Characteristics**  $(\text{Ta} = 25^{\circ}\text{C})$ 

Product Name	V <sub>OUT</sub> [V] (Ta = 25°C)			V <sub>OUT</sub> [V] (Ta = -40 to 105°C)			V <sub>DIF</sub> [V] (I <sub>out</sub> = 300 mA)		V <sub>DIF</sub> [V] (I <sub>out</sub> = 1 A)	
	MIN.	TYP.	MAX.	MIN.	TYP.	MAX.	TYP.	MAX.	TYP.	MAX.
RP132x08xx	0.785	0.800	0.815	0.771	0.800	0.829	0.67	0.89	1.20	1.54
RP132x12xx	1.185	1.200	1.215	1.171	1.200	1.229	0.36	0.54	0.90	1.23
RP132x15xx	1.485	1.500	1.515	1.471	1.500	1.529				
RP132x18xx	1.782	1.800	1.818	1.766	1.800	1.834	0.24	0.33	0.78	1.05
RP132x25xx	2.475	2.500	2.525	2.453	2.500	2.548				
RP132x30xx	2.970	3.000	3.030	2.943	3.000	3.057	0.15	0.21	0.52	0.72
RP132x33xx	3.267	3.300	3.333	3.237	3.300	3.363	0.13	0.18	0.46	0.68
RP132x50xx	4.950	5.000	5.050	4.905	5.000	5.095				
RP132x10xx5	1.035	1.050	1.065	1.021	1.050	1.079	0.51	0.73	1.05	1.39

---

$V_{IN} = V_{SET} + 1.0V$ ,  $I_{OUT} = 1mA$ ,  $C_{IN} = 2.2\mu F$ ,  $C_{OUT} = 2.2\mu F$  ( $V_{OUT} \leq 3.6V$ ),  $4.7\mu F$  ( $V_{OUT} > 3.6V$ ), unless otherwise noted.  
The specifications surrounded by   are guaranteed by design engineering at  $-40^{\circ}C \leq Ta \leq 105^{\circ}C$ .

### • RP132x001B/D (-AE) (Adjustable Output Voltage Type)

(Ta=25°C)

Symbol	Item	Conditions		Min.	Typ.	Max.	Unit	
$V_{FB}$	Feedback Voltage	Ta=25°C	$V_{OUT}=V_{FB}$	0.785	0.800	0.815	V	
		-40°C ≤ Ta ≤ 105°C		0.771		0.829		
$V_{OUT}$	Output Voltage Adjusting Range			0.8		5.5	V	
$I_{LIM}$	Output Current Limit	$V_{OUT}=V_{FB}$		1			A	
$\Delta V_{OUT}/\Delta V_{IN}$	Load Regulation	0.1mA ≤ $I_{OUT}$ ≤ 300mA		3	20	60	mV	
		0.1mA ≤ $I_{OUT}$ ≤ 1A			5			
$V_{DIF}$	Dropout Voltage	$V_{OUT}=V_{FB}$	$I_{OUT}=300mA$	0.67	0.89	1.54	V	
			$I_{OUT}=1A$		1.20			
$I_{SS}$	Supply Current	$V_{OUT}=V_{FB}$ , $I_{OUT}=0mA$ ( $V_{IN}=6.5V$ )			65	85	μA	
$I_{STANDBY}$	Standby Current	$V_{CE}=0V$ , $V_{IN}=6.5V$			0.15	0.60	μA	
$\Delta V_{OUT}/\Delta V_{IN}$	Line Regulation	$V_{OUT}=V_{FB}$ , $1.6V \leq V_{IN} \leq 6.5V$			0.05	0.10	%/V	
$I_{SC}$	Short Current Limit	$V_{OUT}=V_{FB}=0V$			250		mA	
$I_{PD}$	CE Pull-down Current				0.3	0.7	μA	
$V_{CEH}$	CE Input Voltage "H"			1.0			V	
$V_{CEL}$	CE Input Voltage "L"					0.4	V	
$T_{TSD}$	Thermal Shutdown Detection Temperature	Junction Temperature			165		°C	
$T_{TSR}$	Thermal Shutdown Released Temperature	Junction Temperature			95		°C	
$R_{LOW}$	Low Output Nch Tr. ON Resistance (D version)	$V_{IN}=4.0V$ , $V_{CE}=0V$			50		Ω	

All test items listed under Electrical Characteristics are done under the pulse load condition ( $T_j \approx Ta = 25^{\circ}C$ ) except for Dropout Voltage and Load Regulation at 1A Output Current.

---

**RP132x**

NO.EC-265-190408

$V_{IN} = V_{SET} + 1.0V$ ,  $I_{OUT} = 1mA$ ,  $C_{IN} = 2.2\mu F$ ,  $C_{OUT} = 2.2\mu F$  ( $V_{OUT} \leq 3.6V$ ),  $4.7\mu F$  ( $V_{OUT} > 3.6V$ ), unless otherwise noted.  
The specifications surrounded by   are guaranteed by design engineering at  $-40^{\circ}C \leq Ta \leq 105^{\circ}C$ .

**• RP132xxxxB/D (-JE) (Fixed Output Voltage Type)**

(-40°C ≤ Ta ≤ 105°C)

Symbol	Item	Conditions		Min.	Typ.	Max.	Unit
$V_{OUT}$	Output Voltage	$T_a=25^{\circ}C$	$V_{SET} > 1.5V$	$\times 0.99$		$\times 1.01$	V
			$V_{SET} \leq 1.5V$	-15		15	mV
		$-40^{\circ}C \leq Ta \leq 105^{\circ}C$	$V_{SET} > 1.5V$	$\times 0.981$		$\times 1.019$	V
			$V_{SET} \leq 1.5V$	-29		29	mV
$I_{LIM}$	Output Current Limit			1			A
$\Delta V_{OUT} / \Delta I_{OUT}$	Load Regulation	$0.1mA \leq I_{OUT} \leq 300mA$			3	20	mV
		$0.1mA \leq I_{OUT} \leq 1A$			5	60	
$V_{DIF}$	Dropout Voltage	Refer to the <i>Product-specific Electrical Characteristics</i>					
$I_{SS}$	Supply Current	$I_{OUT}=0mA$ ( $V_{IN}=6.5V$ )			65	85	$\mu A$
$I_{standby}$	Standby Current	$V_{CE}=0V$ , $V_{IN}=6.5V$	$T_a=25^{\circ}C$		0.15	0.6	$\mu A$
			$-40^{\circ}C \leq Ta \leq 105^{\circ}C$			4.0	$\mu A$
$\Delta V_{OUT} / \Delta V_{IN}$	Line Regulation	$V_{SET}+0.5V \leq V_{IN} \leq 6.5V$ , * However, $V_{IN} \geq 1.6V$			0.05	0.10	%/V
$I_{SC}$	Short Current Limit	$V_{OUT}=0V$			250		mA
$I_{PD}$	CE Pull-down Current				0.3	0.7	$\mu A$
$V_{CEH}$	CE Input Voltage "H"			1.0			V
$V_{CEL}$	CE Input Voltage "L"					0.4	V
$T_{TSD}$	Thermal Shutdown Detection Temperature	Junction Temperature			165		$^{\circ}C$
$T_{TSR}$	Thermal Shutdown Released Temperature	Junction Temperature			95		$^{\circ}C$
$R_{LOW}$	Low Output Nch Tr. ON Resistance (D version)	$V_{IN}=4.0V$ , $V_{CE}=0V$			50		$\Omega$

All test items listed under Electrical Characteristics are done except for Dropout Voltage and Load Regulation at 1A Output Current.

The specifications surrounded by   are guaranteed by design engineering at  $-40^{\circ}\text{C} \leq \text{Ta} \leq 105^{\circ}\text{C}$ .

**RP132xxxxB/D (-JE) (Fixed Output Voltage Type) Product-specific Electrical Characteristics**  $(-40^{\circ}\text{C} \leq \text{Ta} \leq 105^{\circ}\text{C})$

Product Name	$V_{\text{OUT}} [\text{V}]$ ( $\text{Ta} = 25^{\circ}\text{C}$ )			$V_{\text{OUT}} [\text{V}]$ ( $\text{Ta} = -40$ to $105^{\circ}\text{C}$ )			$V_{\text{DIF}} [\text{V}]$ ( $I_{\text{out}} = 300 \text{ mA}$ )		$V_{\text{DIF}} [\text{V}]$ ( $I_{\text{out}} = 1 \text{ A}$ )	
	MIN.	TYP.	MAX.	MIN.	TYP.	MAX.	TYP.	MAX.	TYP.	MAX.
RP132x08xx	0.785	0.800	0.815	0.771	0.800	0.829	0.67	0.89	1.20	<span style="border: 1px solid black; padding: 0 2px;">1.54</span>
RP132x12xx	1.185	1.200	1.215	1.171	1.200	1.229	0.36	0.54	0.90	<span style="border: 1px solid black; padding: 0 2px;">1.23</span>
RP132x15xx	1.485	1.500	1.515	1.471	1.500	1.529				
RP132x18xx	1.782	1.800	1.818	1.766	1.800	1.834	0.24	0.33	0.78	<span style="border: 1px solid black; padding: 0 2px;">1.05</span>
RP132x25xx	2.475	2.500	2.525	2.453	2.500	2.548				
RP132x30xx	2.970	3.000	3.030	2.943	3.000	3.057	0.15	0.21	0.52	<span style="border: 1px solid black; padding: 0 2px;">0.72</span>
RP132x33xx	3.267	3.300	3.333	3.237	3.300	3.363	0.13	0.18	0.46	<span style="border: 1px solid black; padding: 0 2px;">0.68</span>
RP132x50xx	4.950	5.000	5.050	4.905	5.000	5.095				
RP132x10xx5	1.035	1.050	1.065	1.021	1.050	1.079	0.51	0.73	1.05	<span style="border: 1px solid black; padding: 0 2px;">1.39</span>

---

**RP132x**

NO.EC-265-190408

$V_{IN} = V_{SET} + 1.0V$ ,  $I_{OUT} = 1mA$ ,  $C_{IN} = 2.2\mu F$ ,  $C_{OUT} = 2.2\mu F$  ( $V_{OUT} \leq 3.6V$ ),  $4.7\mu F$  ( $V_{OUT} > 3.6V$ ), unless otherwise noted.  
The specifications surrounded by   are guaranteed by design engineering at  $-40^{\circ}C \leq Ta \leq 105^{\circ}C$ .

**• RP132x001B/D (-JE) (Adjustable Output Voltage Type)**

(-40°C ≤ Ta ≤ 105°C)


Symbol	Item	Conditions		Min.	Typ.	Max.	Unit	
$V_{FB}$	Feedback Voltage	Ta=25°C	$V_{OUT}=V_{FB}$	0.785	0.800	0.815	V	
		-40°C ≤ Ta ≤ 105°C		0.771		0.829		
$V_{OUT}$	Output Voltage Adjusting Range			0.8		5.5	V	
$I_{LIM}$	Output Current Limit	$V_{OUT}=V_{FB}$		1			A	
$\Delta V_{OUT} / \Delta I_{OUT}$	Load Regulation	0.1mA ≤ $I_{OUT}$ ≤ 300mA		3	20	60	mV	
		0.1mA ≤ $I_{OUT}$ ≤ 1A			5			
$V_{DIF}$	Dropout Voltage	$V_{OUT}=V_{FB}$	I <sub>OUT</sub> =300mA	0.67	0.89	1.54	V	
			I <sub>OUT</sub> =1A		1.20			
I <sub>SS</sub>	Supply Current	$V_{OUT}=V_{FB}$ , $I_{OUT}=0mA$ ( $V_{IN}=6.5V$ )			65	85	μA	
I <sub>standby</sub>	Standby Current	$V_{CE}=0V$ , $V_{IN}=6.5V$	Ta=25°C	0.15	0.6	4.0	μA	
			-40°C ≤ Ta ≤ 105°C					
$\Delta V_{OUT} / \Delta V_{IN}$	Line Regulation	$V_{OUT}=V_{FB}$ , 1.6V ≤ $V_{IN}$ ≤ 6.5V			0.05	0.10	%/V	
I <sub>SC</sub>	Short Current Limit	$V_{OUT}=V_{FB}=0V$			250		mA	
I <sub>PD</sub>	CE Pull-down Current				0.3	0.7	μA	
$V_{CEH}$	CE Input Voltage "H"			1.0			V	
$V_{CEL}$	CE Input Voltage "L"					0.4	V	
T <sub>TSD</sub>	Thermal Shutdown Detection Temperature	Junction Temperature			165		°C	
T <sub>TSR</sub>	Thermal Shutdown Released Temperature	Junction Temperature			95		°C	
R <sub>LOW</sub>	Low Output Nch Tr. ON Resistance (D version)	$V_{IN}=4.0V$ , $V_{CE}=0V$			50		Ω	

All test items listed under Electrical Characteristics are done except for Dropout Voltage and Load Regulation at 1A Output Current.


---

## TYPICAL APPLICATION


Fixed Output Voltage Type (HSOP-6J/ SOT-89-5)



Fixed Output Voltage Type (TO-252-5-P2)



Adjustable Output Voltage Type (HSOP-6J / SOT-89-5/ TO-252-5-P2)



## TECHNICAL NOTES

### Phase Compensation

In these ICs, phase compensation is made for securing stable operation even if the load current is varied. For this purpose, use a capacitor C2 with good frequency characteristics and ESR (Equivalent Series Resistance).

If a tantalum capacitor is used, and its ESR of C2 is large, the loop oscillation may result. Because of this, select C2 carefully considering its frequency characteristics.

**Recommended value of the external capacitors**

V <sub>OUT</sub>	Capacitors	
V <sub>SET</sub> ≤ 3.6V	C1	2.2μF
	C2	2.2μF
V <sub>SET</sub> > 3.6V	C1	2.2μF
	C2	4.7μF

Please refer to "Technical Notes on Adjustable Output Voltage Type" when using R1 and R2 as output capacitors.

### PCB Layout

Make V<sub>DD</sub> and GND lines sufficient. If their impedance is high, noise pickup or unstable operation may result. Connect a capacitor C1 between V<sub>DD</sub> and GND pin with a capacitance value as "Recommendation value of the external capacitors" above or more, and as close as possible to the pins.


Set external components, especially the output capacitor C2, as close as possible to the ICs, and make wiring as short as possible.

### Transient Response


When using the Adjustable Output Voltage Type, the transient response could be affected by the external resistors. Evaluate the circuit taking the actual conditions of use into account.

## TYPICAL APPLICATION FOR IC CHIP BREAKDOWN PREVENTION


### Fixed Output Voltage Type (HSOP-6J / SOT-89-5)



### Fixed Output Voltage Type (TO-252-5-P2)



### Adjustable Output Voltage Type (HSOP-6J / SOT-89-5/ TO-252-5-P2)




When a sudden surge of electrical current travels along the  $V_{OUT}$  pin and GND due to a short-circuit, electrical resonance of a circuit involving an output capacitor ( $C_2$ ) and a short circuit inductor generates a negative voltage and may damage the device or the load devices. Connecting a schottky diode ( $D_1$ ) between the  $V_{OUT}$  pin and GND has the effect of preventing damage to them.

## ADJUSTABLE OUTPUT VOLTAGE TYPE SETTINGS

### Output Voltage Setting Method

Adjustable Output Voltage Type can be adjusted the output voltage up to 5.5V by using the external divider resistors. Also, please use  $16\text{k}\Omega$  or less for R2 resistor.

If the  $V_{FB}$  voltage is described as  $\text{set}V_{FB}$ , the output voltage can be set by using the following equations  
 $\text{Set}V_{FB}$  is equal to 0.8V. The  $V_{OUT}$  pin of Adjustable Output Voltage Type should be connected to the  $V_{FB}$  pin.



$$I_1 = I_{IC} + I_2 \dots \quad (1)$$

$$I_2 = \text{set}V_{FB} / R_2 \dots \quad (2)$$

Thus,

$$I_1 = I_{IC} + \text{set}V_{FB} / R_2 \dots \quad (3)$$

Therefore,

$$V_{OUT} = \text{set}V_{FB} \times R_1 \times I_1 \dots \quad (4)$$

Put Equation (3) into Equation (4), then

$$\begin{aligned} V_{OUT} &= \text{set}V_{FB} + R_1 (I_{IC} + \text{set}V_{FB} / R_2) \\ &= \text{set}V_{FB} \times (1 + R_1 / R_2) + R_1 \times I_{IC} \end{aligned} \dots \quad (5)$$

In Equation (5),  $R_1 \times I_{IC}$  is the error-causing factor in  $V_{OUT}$ .

As for  $I_{IC}$ ,

$$I_{IC} = \text{set}V_{FB} / R_{IC} \dots \quad (6)$$

Therefore, the error-causing factor  $R_1 \times I_{IC}$  can be described as follows.

$$\begin{aligned} R_1 \times I_{IC} &= R_1 \times \text{set}V_{FB} / R_{IC} \\ &= \text{set}V_{FB} \times R_1 / R_{IC} \end{aligned} \dots \quad (7)$$

For better accuracy, choosing  $R_1 (<< R_{IC})$  reduces this error.

Without the error-causing factor  $R_1 \times I_{IC}$ , the output voltage can be calculated by the following equation

$$V_{OUT} = \text{set}V_{FB} \times ((R_1 + R_2) / R_2) \dots \quad (8)$$

$R_{IC}$  of RP132x is approximately Typ.  $1.3\text{M}\Omega$  ( $T_a=25^\circ\text{C}$ , this value is guaranteed by design).

The value could be affected by the temperature, therefore evaluate the circuit taking the actual conditions of use into account.

## **INRUSH CURRENT LIMIT TIME SETTINGS**

The RP132x Series include the circuit which can limit the inrush current at start-up to 500mA or less. The current limit time of B/D version is fixed internally as approximately Typ.500μs.

Please note that during the inrush current limit time, the load current cannot be more than the limited current.

## PACKAGE INFORMATION

### POWER DISSIPATION (SOT-89-5)

The power dissipation of the package is dependent on PCB material, layout, and environmental conditions. The following measurement conditions are based on JEDEC STD. 51-7.

#### Measurement Conditions

Item	Measurement Conditions
Environment	Mounting on Board (Wind Velocity = 0 m/s)
Board Material	Glass Cloth Epoxy Plastic (Four-Layer Board)
Board Dimensions	76.2 mm × 114.3 mm × 0.8 mm
Copper Ratio	Outer Layer (First Layer): Less than 95% of 50 mm Square Inner Layers (Second and Third Layers): Approx. 100% of 50 mm Square Outer Layer (Fourth Layer): Approx. 100% of 50 mm Square
Through-holes	Ø 0.3 mm × 13 pcs


#### Measurement Result

(Ta = 25°C, Tjmax = 150°C)


Item	Measurement Result
Power Dissipation	3200 mW
Thermal Resistance ( $\theta_{ja}$ )	$\theta_{ja} = 38^\circ\text{C}/\text{W}$
Thermal Characterization Parameter ( $\psi_{jt}$ )	$\psi_{jt} = 13^\circ\text{C}/\text{W}$

$\theta_{ja}$ : Junction-to-Ambient Thermal Resistance

$\psi_{jt}$ : Junction-to-Top Thermal Characterization Parameter




Power Dissipation vs. Ambient Temperature



Measurement Board Pattern

## PACKAGE DIMENSIONS (SOT-89-5)



SOT-89-5 Package Dimensions

## POWER DISSIPATION (HSOP-6J)

The power dissipation of the package is dependent on PCB material, layout, and environmental conditions. The following measurement conditions are based on JEDEC STD. 51-7.

### Measurement Conditions

Item	Measurement Conditions
Environment	Mounting on Board (Wind Velocity = 0 m/s)
Board Material	Glass Cloth Epoxy Plastic (Four-Layer Board)
Board Dimensions	76.2 mm × 114.3 mm × 0.8 mm
Copper Ratio	Outer Layer (First Layer): Less than 95% of 50 mm Square Inner Layers (Second and Third Layers): Approx. 100% of 50 mm Square Outer Layer (Fourth Layer): Approx. 100% of 50 mm Square
Through-holes	Ø 0.3 mm × 28 pcs


### Measurement Result

(Ta = 25°C, Tjmax = 150°C)


Item	Measurement Result
Power Dissipation	3400 mW
Thermal Resistance ( $\theta_{ja}$ )	$\theta_{ja} = 37^\circ\text{C/W}$
Thermal Characterization Parameter ( $\psi_{jt}$ )	$\psi_{jt} = 7^\circ\text{C/W}$

$\theta_{ja}$ : Junction-to-Ambient Thermal Resistance

$\psi_{jt}$ : Junction-to-Top Thermal Characterization Parameter




Power Dissipation vs. Ambient Temperature



Measurement Board Pattern

## PACKAGE DIMENSIONS (HSOP-6J)



HSOP-6J Package Dimensions

## POWER DISSIPATION (TO-252-5-P2)

The power dissipation of the package is dependent on PCB material, layout, and environmental conditions. The following measurement conditions are based on JEDEC STD. 51-7.

### Measurement Conditions

Item	Measurement Conditions
Environment	Mounting on Board (Wind Velocity = 0 m/s)
Board Material	Glass Cloth Epoxy Plastic (Four-Layer Board)
Board Dimensions	76.2 mm × 114.3 mm × 0.8 mm
Copper Ratio	Outer Layer (First Layer): Less than 95% of 50 mm Square Inner Layers (Second and Third Layers): Approx. 100% of 50 mm Square Outer Layer (Fourth Layer): Approx. 100% of 50 mm Square
Through-holes	Ø 0.3 mm × 21 pcs


### Measurement Result

(Ta = 25°C, Tjmax = 150°C)


Item	Measurement Result
Power Dissipation	4800 mW
Thermal Resistance ( $\theta_{ja}$ )	$\theta_{ja} = 26^\circ\text{C/W}$
Thermal Characterization Parameter ( $\psi_{jt}$ )	$\psi_{jt} = 7^\circ\text{C/W}$

$\theta_{ja}$ : Junction-to-Ambient Thermal Resistance

$\psi_{jt}$ : Junction-to-Top Thermal Characterization Parameter




Power Dissipation vs. Ambient Temperature



Measurement Board Pattern

## PACKAGE DIMENSIONS (TO-252-5-P2)







\* ) The tab on the bottom of the package enhances thermal performance and is electrically connected to GND (substrate level). It is recommended that the tab be connected to the ground plane on the board, or otherwise be left floating.

(Unit : mm)



## TYPICAL CHARACTERISTICS



Note: Typical Characteristics are intended to be used as reference data; they are not guaranteed.

### 1) Output Voltage vs. Input Voltage ( $T_a=25^\circ C$ )





**RP132x08xx****RP132x15xx****RP132x33xx****RP132x55xx**







### 2) Supply Current vs. Input Voltage ( $T_a=25^\circ C$ )






**RP132x08xx****RP132x15xx**







**RP132x33xx****RP132x55xx**





### 3) Supply Current vs. Temperature







**RP132x08xx****RP132x15xx****RP132x33xx****RP132x55xx**

**4) Output Voltage vs. Temperature****RP132x08xx****RP132x15xx****RP132x33xx****RP132x55xx****5) Dropout Voltage vs. Output Current****RP132x08xx****RP132x15xx**


**RP132x33xx****RP132x55xx****6) Dropout Voltage vs. Set Output Voltage****7) Ripple Rejection vs. Input Voltage (C1=none, Ripple=0.2Vp-p, Ta=25°C)****RP132x33xx****RP132x33xx**

**RP132x33xx****RP131x55xx****RP132x55xx****RP132x55xx****8) Ripple Rejection vs. Frequency (C1=none, Ta=25°C)****RP132x08xx****RP132x33xx**


**RP132x551x****9) Input Transient Response (C1=none, Iout=100mA, tr=tf=5 $\mu$ s, Ta=25°C)****RP132x08xx****RP132x33xx****RP132x55xx**

**10) Load Transient Response ( $V_{IN}=V_{OUT}+1.0V$ ,  $C1=\text{Ceramic } 2.2\mu\text{F}$ ,  $tr=tf=0.5\mu\text{s}$ ,  $T_a=25^\circ\text{C}$ )****RP132x08xx****RP132x08xx****RP132x08xx****RP132x33xx****RP132x33xx****RP132x33xx**


RP132x55xx



RP132x55xx




RP132x55xx








### 11) Turn on Speed with CE pin (C1=Ceramic 2.2 $\mu$ F, Ta=25°C)

RP132x08xx




RP132x33xx




**RP132x55xx****12) Turn off Speed with CE pin (D version) (C1=Ceramic 2.2 $\mu$ F, Ta=25°C)****RP132x08xD****RP132x33xD****RP132x55xD**

### 13) Inrush Current (C1=Ceramic 2.2μF, I<sub>OUT</sub>=100mA, Ta=25°C)


RP132x08xx



RP132x33xx




RP132x55xx



### 14) Minimum Operating Voltage

RP132x08xx



The operation range that can output 0.8V is shown by the hatched area in the graph.

## ESR vs. Output Current

When using these ICs, consider the following points:

The relations between  $I_{OUT}$  (Output Current) and ESR of an output capacitor are shown below.

The conditions when the white noise level is under  $40\mu V$  (Avg.) are marked as the hatched area in the graph.

### Measurement Conditions

Frequency Band : 10Hz to 2MHz


Temperature :  $-40^{\circ}C$  to  $85^{\circ}C$

Hatched Area : Noise level is under  $40\mu V$ ms (Avg.)


C1 :  $2.2\mu F$  (Kyocera CM05X5R225M06A)

C2 :  $2.2\mu F$  ( $V_{OUT} = 0.8V$ , Kyocera CM105X5R225K06AB)  
 $4.7\mu F$  ( $V_{OUT} = 5.5V$ , Kyocera CM105X5R475M06AB)

**RP132x08xx**



**RP132x55xx**





1. The products and the product specifications described in this document are subject to change or discontinuation of production without notice for reasons such as improvement. Therefore, before deciding to use the products, please refer to our sales representatives for the latest information thereon.
2. The materials in this document may not be copied or otherwise reproduced in whole or in part without prior written consent of our company.
3. Please be sure to take any necessary formalities under relevant laws or regulations before exporting or otherwise taking out of your country the products or the technical information described herein.
4. The technical information described in this document shows typical characteristics of and example application circuits for the products. The release of such information is not to be construed as a warranty of or a grant of license under our company's or any third party's intellectual property rights or any other rights.
5. The products in this document are designed for automotive applications. However, when using the products for automotive applications, please make sure to contact our sales representative in advance due to confirming the quality level.
6. We are making our continuous effort to improve the quality and reliability of our products, but semiconductor products are likely to fail with certain probability. In order to prevent any injury to persons or damages to property resulting from such failure, customers should be careful enough to incorporate safety measures in their design, such as redundancy feature, fire containment feature and fail-safe feature. We do not assume any liability or responsibility for any loss or damage arising from misuse or inappropriate use of the products.
7. Anti-radiation design is not implemented in the products described in this document.
8. The X-ray exposure can influence functions and characteristics of the products. Confirm the product functions and characteristics in the evaluation stage.
9. WLCSP products should be used in light shielded environments. The light exposure can influence functions and characteristics of the products under operation or storage.
10. There can be variation in the marking when different AOI (Automated Optical Inspection) equipment is used. In the case of recognizing the marking characteristic with AOI, please contact our sales or our distributor before attempting to use AOI.
11. Please contact our sales representatives should you have any questions or comments concerning the products or the technical information.



**Nisshinbo Micro Devices Inc.**

**Official website**

<https://www.nisshinbo-microdevices.co.jp/en/>

**Purchase information**

<https://www.nisshinbo-microdevices.co.jp/en/buy/>