

		REVISIONS												
ISS	ZONE	DESCRIPTION\PER REQUEST\DATE												
					<p>NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)</p> <p>1. BRASS PER QQ-B-626 2. BRASS PER QQ-B-613 3. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE 4. NICKEL PL. 200 MIN. THICK OVER COPPER STRIKE 5. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE 6. JIS H 3250, C 2700</p> <p>1. CRIMPED FERRULE HEX CRIMP SIZE .213" 2. CRIMPED CONTACT PIN HEX CRIMP SIZE .068"</p>									
9	FERRULE	NOTE 6	NOTE 3	1	FR-635/56X127					PART NO. B1121A1-ND3G-1A-50		Amphenol		
8	CONTACT PIN	NOTE 1	NOTE 5	1	B50000-8-25/1	DIMENSIONS ARE IN MILLIMETERS				APPROVED	DATE 10-11-01'			
7	WASHER	NOTE 2	NOTE 3	1	WS-128/9X08	UNLESS OTHERWISE SPECIFIED TOLERANCES				CHECKED	DATE 10-11-01'	TITLE BNC CRIMP PLUG		
6	SPRING	SK5	NOTE 4	1	B50000-6	0.5-6 = ±0.2				DRAWN	DATE 10-11-01'	DRAWING NO. KJ-B1121A1-ND3G-223U-50		
5	RETAINER RING	NOTE 1	NOTE 3	1	B50000-5	6-30 = ±0.4						ITEM NO.		
4	GASKET	RUBBER	RED	1	GS-115/8X15	30-120 = ±0.6								
3	INSULATOR	DELIN	NATURAL	1	B50000-3-50-A	120-315 = ±1								
2	BODY	NOTE 1	NOTE 3	1	B50000-2-427/31	315-1000 = ±1.6								
1	SHELL	NOTE 1	NOTE 3	1	B50000-1-B	1000-2000 = ±2.4								
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE	3/1	ISSUE	A	FILE NO.				

Amphenol

TITLE BNC CRIMP PLUG
DRAWING NO. KJ-B1121A1-ND3G-223U-50
ITEM NO.