# ADAME ETECH



FAKRA SERIES





# **FAKRA Series**

Adam Tech's FAKRA series is composed of various generations of the FAKRA (Fachkreis Automobile) standard, including High Speed Data and Mini FAKRA. Each FAKRA connector is embedded within a special color-code plastic housing that contains a locking feature with an audible clicking noise, which confirms the connection. These connectors are used for both board and cable mounting, with a variety of cable assemblies available. All Adam Tech FAKRA products are RoHS compliant.

# **Series Outline:**

- High Spead Mini FAKRA (AM and BM)
- High Speed Data FAKRA
- Waterproof FAKRA Cable Assemblies
- Standard FAKRA

1

Code (X)	Applications	Color/RAL	
Α	Radio without phantom supply	Jet Black / 9005	
В	Radio with phantom supply	Cream White / 9001	
С	GPS: telematics or navigation	Signal Blue / 5005	
D	GSM	Claret Violet / 4004	
E	TV1 / SDARS	Leaf Green / 6002	
F	TV2 / SDARS	Nut Brown / 8011	
G	Remote keyless entry	Blue Gray / 7031	
н	GPS: telematics and navigation	Heather Violet / 4003	
J	Bluetooth / controlled parking / heating	Beige / 1001	
К	Radio with IF	Curry / 1027	
L	Not defined	Yellow Green / 6018	
M	Not defined	Pastel Orange / 2003	
0	Not defined	Light Green / 6027	
Z	Neutral coding	Water Blue / 5021	



















# **High Speed Mini FAKRA**





Adam Tech's FAKRA series is headlined by High Speed Mini FAKRA Connectors and Cable Assemblies. These products support data transmission rates up to 20 Gbps, and frequencies up to 9 GHz. Designed with space saving in mind, they require 80% less installation space than standard FAKRAs. Adam Tech's offering is composed of two styles: AM and BM. Between the two styles a variety of color-coded connectors and cable assemblies are available, including board side plugs, double-ended mini FAKRA jack cable assemblies, and mini FAKRA to SMA cable assemblies. Mini FAKRA to standard FAKRA cable assemblies are also available, bridging the gap between the two generations.

# **APPLICATIONS:**

- Automotive
- Autonomous driving (ADAS)
- 4k 360° surround cameras
- 4k high resolution displays
- Sensors
- Remote start and keyless entry
- Infotainment systems
- 3D instrument clusters
- GPS
- · Satellite radios





- High speed data transmission rates up to 20 Gbps
- Frequency: DC up to 9.0 GHz
- 1x1 and 2x2 plugs and jacks
- Color coded mechanical layouts
- Space saving design
- Mini FAKRA cable to board connection system
- Mini FAKRA to SMA capabilities
- Mini FAKRA to standard FAKRA capabilities

#### **SPECIFICATIONS:**

#### **Material:**

Insulator: Thermoplastic Contacts: Brass

Shell: Zamak, tin plated

#### **Contact Plating:**

Contact area: 80 - 160u" silver plated Solder tails: 80 - 160u" tin plated

Underplate: 40 - 160u" nickel underplate overall

#### **Electrical:**

Impedance: 50 Ohm Frequency: DC to 9 GHz

Return loss: ≥ 17 dB to 6 GHz or ≥ 12 dB to 9 GHz

Insertion loss:  $\leq$  0.75 dB @ 9 GHz Insulation resistance: 1000 M $\Omega$ 

#### **Mechanical:**

Mating cycles: ≥ 25 cycles Engagement force: ≤ 30N Disengagement force: ≥ 60N

#### **Temperature Rating:**

Operating temperature range: -40°C to +105°C









































































# **High Speed Data FAKRA**



Adam Tech's High Speed Data FAKRA series is composed of four pin connectors equipped with a 100 ohm impedance controlled system, offering high speeds and top-quality signal transmission. Designed to satisfy RF requirements in various telematic and multimedia applications, these connectors provide high performance, cost effective RF interface to FAKRA and USCAR standards. Their SMB based design includes multiple color-coded plastic housings to ensure accurate connections, as well as to meet automotive specifications. Adam Tech's HSD FAKRA connectors are ideal for automotive applications, meeting the operational and environmental requirements of Satellite Digital Audio Radio Service (SDARS), Global System for Mobile Communications (GSM), and Global Positioning System (GPS).

adam-tech.com

#### FEATURES AND BENEFITS:

- High speed data transmission rates up to 6 Gbps
- Frequency: DC up to 2.0 GHz
- 100 ohm differential impedance
- 4 pins
- Color-coded mechanical layouts
- Locking feature
- Selective gold plating
- Shielded for EMI/RFI protection
- Multiple connector configurations including straight, right angle, and cable mount

# **APPLICATIONS:**

- Automotive
- GPS
- Bluetooth
- Keyless entry
- **Telematics**
- Outdoor routers
- Satellite radios
- Infotainment systems
- Medical devices
- Machines with RF interfacing
- High tech applications
- Harsh environment

















6







Right Angle PCB Plug

# HSD-04X-S-PRB-SG-C1-TR



Right Angle PCB Plug (Reverse)

# HSD-04X-S-PT-SG-C1-TR



Straight PCB Plug

# HSD-04X-S-SD-SG-C4



Solder Cable Socket

# **SPECIFICATIONS:**

# **Material:**

Plugs: Insulator: PA Contacts: Brass

Outer contacts: Zinc alloy

Sockets:

Insulator: PBT, rated UL 94V-0 Contacts: Phosphor bronze Contact sleeve: Phosphor bronze

Outer contacts: Brass

# **Contact Plating:**

Contact area: Selective gold plated Solder tails area: Tin plated

# **Electrical:**

Impedance, differential mode: 100  $\Omega$  differential signaling, for one pair or quad cable shielded

Frequency: DC to 2.0 GHz

Return loss: ≥ 20 dB to 1.0 GHz or ≥ 17 dB to 2.0 GHz

Insertion loss:  $\leq$  0.1 dB @ 1.0 GHz Insulation resistance: 1000 M $\Omega$  Signal contact resistance: 10 m $\Omega$ 

# Mechanical:

Mating cycles: ≥ 25 cycles Engagement force: ≤ 30N Disengagement force: ≥ 5N Retention force latch: ≥ 110N Coding efficiency: ≥ 80N

### **Temperature Rating:**

Operating temperature range: -40°C to +105°C

















# Waterproof FAKRA Cable Assemblies

Adam Tech's Waterproof FAKRA Cable Assemblies are available in ratings of IP69K, IP67, and IPX7. The double-ended FAKRA cables are offered as jack to jack, plug to plug, and jack to plug configurations. FAKRA plug to IPEX cable assemblies are also available. These assemblies are offered in a variety of cable types, and lengths ranging from 0.1m to 5m. The series includes a line of non-waterproof options, ranging in cable configuration, type, and length.

#### **FEATURES AND BENEFITS:**

- · Waterproof ratings: IP69K, IP67, and IPX7
- Various cable assembly configurations including double-ended FAKRA and FAKRA to IPEX
- Cable types: RTK-031, RG-174, RG-316U, and O.D. 1.37mm coaxial
- Cable lengths: 0.1m, 0.3m, 0.6m, 1m, 2m, 3m, 4m, and 5m
- · Straight and right angle connectors
- Non-waterproof options available
- · Color coded mechanical layouts

# **APPLICATIONS:**

- Automotive
- Bluetooth
- Remote start and keyless entry
- Infotainment systems
- GPS
- Climate controls
- Satellite radios
- · Vehicle cameras

# **SPECIFICATIONS:**

#### **Connector:**

Insulator: Thermoplastic Contacts: Brass, gold plated

#### Cable:

Wire spec: RTK-031, RG-174, RG-316U

Wire gauge: 22-30 AWG

#### **Electrical:**

Impedance: 50 Ohm

#### **Temperature Rating:**

Operating temperature range: -40°C to +105°C













































































# Standard FAKRA

Adam Tech's Standard FAKRA series is composed of SMA and SMB automotive-grade connectors that can operate up to 6 GHz. These board and cable mount connectors, are offered in both vertical and right angle orientations. Waterproof FAKRAs are also available, with an IP67 rating.

# **FEATURES AND BENEFITS:**

- Frequency: DC up to 4.0 GHz
- · Color coded mechanical layouts
- SMA and SMB
- Board and cable mount
- · Vertical and right angle
- Body options



# **APPLICATIONS:**

- Automotive
- Bluetooth
- Remote start and keyless entry
- Infotainment systems
- GPS
- Climate controls
- Satellite radios
- Vehicle cameras



# **SPECIFICATIONS:**

# **Material:**

Insulator: Thermoplastic (PTFE)
Pin contact and body: Brass, gold plated

Shell: PA66

#### **Electrical:**

Impedance: 50 Ohm Frequency: DC~4 GHz Withstanding voltage: 335 V Insulation resistance: 1000 M $\Omega$ 

Contact resistance:  $6~\text{m}\Omega$  max. (center contact)

 $1 \text{ m}\Omega$  max. (outerr contact)

# **Temperature Rating:**

Operating temperature range: -40°C to +85°C

























SMB FAKRA Plug Right Angle Board Mount

# RF55-24X-T-09-50-X-SH



SMB Bulkhead FAKRA Plug Straight Cable Mount - IP54

# RF55-25X-T-00-50-G-SH



SMB FAKRA Plug (Tall Body) Straight Board Mount

# RF55-26X-T-09-50-X-SH



SMB Bulkhead FAKRA Plug Straight Cable Mount - IP67

# RF55-27X-T-02-50-X-SH



SMB FAKRA Plug Straight Cable Mount for Panel

# RF55-28X-T-00-50-G-SH



SMB FAKRA Plug Straight DIP Board Mount



















SMB FAKRA Plug Straight DIP Board Mount

# RF55-30X-T-00-50-G-SH



SMB FAKRA Plug Straight DIP Board Mount

RF55-31X-T-02-50-X-SH



SMB FAKRA Plug Straight Cable Mount

RF55-32X-T-00-50-X-SH



SMB FAKRA Plug (Short Body) Right Angle Board Mount

RF55-33X-T-00-50-X-SH



SMB FAKRA Plug Right Angle Board Mount

# RF55-34X-T-02-50-SH



SMB FAKRA Jack Straight Cable Mount for Panel















# ADAM TECH USA (WORLDWIDE HQ)

909 Rahway Ave. Union, NJ 07083 U.S.A.

Tel: 908-687-5000 Fax: 908-687-5710

Email: info@adam-tech.com

# **ADAM TECH EUROPE**

Marcel Schwob Karlsruhe, Germany Email: info@adam-tech.com

# **ADAM TECH SOUTH AMERICA**

Cesar Nakajune Sao Paolo, Brazil

Email: info@adam-tech.com

# **ADAM TECH TAIWAN**

9F-3, No. 10, Lane 609, Sec. 5, Chongxin Rd. Sanchong Dist., New Taipei City 241 Taiwan (R.O.C.)
Tel: 886-2 2999 8028
Fax: 886-2 2999 8062

Fax: 886-2 2999 8062 Email: info@adam-tech.com

#### **ADAM TECH CHINA**

Yingfeng 1st Road, Dajingtou Community Dalang Town, Dongguan City Guangdong Province China (P.R.C.) Tel: 886-2 2999 8028

Fax: 886-2 2999 8062 Email: info@adam-tech.com

To contact us, scan the QR code to reach our website inquiry form.



adam-tech.com